China Hydraulic Roll Off Hook Lift Garbage Truck 6cmb Swing Arm Garbage Truck Refuse Moving Station For Sale

Basic Information

- Place of Origin:
- Hubei, China
- Brand Name:
- Price:
- jac
- CN¥47,067.15/units 1-4 units



Product Specification

- Video Outgoing-inspection: Provided
- Machinery Test Report: Provided
- Core Components: Engine, Gearbox, Motor

4X2

Compactor

Automatic

Euro 4

Diesel

110

5280

1 Year

3500 Kg

5280

2

- Drive Wheel:
- Type:
- Transmission Type:
- Emission Standard:
- Fuel Type:

Size:

- Engine Capacity:
 - 6920*2100*2520
- Gross Vehicle Weight:
- Warranty:
- Weight (KG):
- Curb Weight(Kg):
- Persons In Cab:



More Images









Product features:

Appearance shape is beautiful and generous, integrated into the city landscape design, colour matching and coordination, to enhance the city image, become a bright city landscape, highlighting the charm of the city.

The compression ratio of the refuse station is as high as 5:1, far exceeding that of similar products, which greatly reduces the volume of rubbish, improves the transport efficiency and optimises the allocation of resources.

Adopting anti-corrosion and wear-resistant surface treatment process to prolong the service life of the equipment, reduce long-term maintenance costs and improve the cost-effectiveness of the equipment.

Product usage:

Widely placed in city squares, park entrances and other public places, taking into account the aesthetics and practicality, to provide a comfortable environment for the public and enhance the quality of life of the public.

In the school campus, to provide teachers and students with a clean learning and living environment, deal with daily rubbish, help campus civilisation construction, and cultivate students' awareness of environmental protection.

Used in the construction site of new urban areas to ensure environmental hygiene during the construction process, promote the orderly development of new areas and lay the foundation for urban development.

Product advantages:

High compression ratio reduces transport costs, improves transport efficiency, optimises resource allocation and improves overall efficiency.

High-quality surface treatment reduces the maintenance frequency, lowers the cost, improves the cost-effectiveness of the equipment, and saves the cost for the users.

After-sales service

AUTOKING has four overseas branches to develop overseas customers. We also carry out after-sales service guarantee for vehicles.

Is the price cheap?

The price is chosen by comparing several car manufacturers, and we also hope that customers can compare several times and finally choose our company.

Is international logistics guaranteed?

After the purchase of goods are shipped, the company tracks the order in full. Shipping video and transport video we provide for you at any time.

Specification:

Overall Dimensions (mm)	4000×2295×2450
Waste bin volume (m ³)	6
Tipping bucket volume (m ³)	3
Max lifting force of tipping bucket (T)	1.5
Feed inlet height (mm)	1600
Bottom beam width (mm)	1060
Guiding wheel track width (mm)	2200







